

LTR 9610_{QUAD}



LAMTRAC



Note: The specifications are given under ideal conditions and on the basis of adequate operator skill and ability.



Dimensions

Track Width	762 mm	30"
Overall Length	7010.4 mm	276"
Overall Width	2578 mm	101.5"
Overall Height	3302 mm	128"
Ground Clearance	508 mm	23"

Dimensions (with Mulcher) 2.25 m

Overall Length	8,686.8 mm	342"
Overall Width	2,641.6 mm	104"
Overall Height	3,302 mm	128"
Ground Clearance	584.2 mm	23"
Weight	23,088 kg	50,900 lbs
Ground Pressure (with 32" standard track)	26.20 kpa	3.9 PSI
Ground Pressure (with 39" LGP track)	19.99 kpa	3.0 PSI

Performance

Speed		
(working mode)	0-5.1 km/h	3.2 mph
(taxi mode)	6.7 km/h	4.2 mph
Climbing/side Hill	45 °(100%)	

Engine

Make	Cummins
Model	QSX-15 Tier III
No. of Cylinder	Six(6)
Displacement	15L
Horsepower	610hp@2100rpm
Torque	1873 ft/lb@1500rpm

Tracks

Steel Single Grouser
Pivoting Undercarriage
Sealed and Lubricated

Capacities

Fuel Tank	984 liters	260 gallons
Hydraulic Tank	284 liters	65 gallons

Electrical

Voltage (Dual)	12 - 24 Volts
Battery Capacity (24 volt)	1800 amps
Alternator (12 volt)	160 amps
Alternator (24 volt)	35 amps

Standard Equipment

Front Equipment Mounting Arms
Digital Display
Lamtronic Monitoring System
ROPS/FOPS/OPS
Joystick Controls
Audio Visual Alarm on Major Components
Electric Cab Tilt
Suspension Seat with Seat Belt
Insulated Cab
Cab Heater/Defrost System/Air Conditioning
Hydraulic Oil Filling Pump Electric
Engine Block Heater
4 Front and 2 Rear Lights 2 Side Lights
Back Up Alarm
Tool Box
Twin Turbo Oven
Rear View Camera
Sirius Satellite Radio

Optional Equipment

Fire Suspension
Hydraulic Winch 30,000 LBS
Hydraulic Tank Heater
Coolant Heater
Positive Air Shut Off
Compressor
L.G.P. track Pad 39"

250 Exportation Street
Tracadie-Sheila, NB
Canada
E1X 1A2

Tel. 1.888.LAMTRAC
Fax. 506.393.8501
www.lamtrac.com