



LAMTRAC



LTR 5200 QUAD

Note: The specifications for a basic vehicle are given on the basis of adequate skills, ability of the operator and under ideal conditions.



Dimensions

Track Width	71 mm	28"
Overall Length (without Blade)	608 mm	240"
Overall Width (without Blade)	250 mm	99"
Overall Height	274 mm	108"
Ground Clearance	41mm	16"
Ground Pressure	10.5 KPa	1.5 psi
Front Blade Width	259 mm	102"
Overall Length (with front blade)	716 mm	282"
Weight (with front Blade)	6793 kgs	14980 lbs

Operators Cab

Width of Cab	2130 mm	84"
Structure	ROPS - Design	

Speed

Low Range	10km/h	6 mph
High Range	25 km/h	15 mph
Inside Turning Radius	3.5 m	11 feet

Engine

Model	Cummins - QSB Tier III	
Displacement	6.7L (409CID)	
Power@2000 rpm	142 kw	190 hp
Torque@1400rpm	931 Nm	687ft/lb

Power Train

Type	Bosch/Rexroth	Hydrostatic
------	---------------	-------------

Steering

Type	Articulation
Control	Steering wheel

Undercarriage

Track	Stretch resistant rubber belts
Crosslink	Steel
Track Pivot	Oscillating

Electrical

System Voltage	24 volts
Accessory Voltage	12 volts
Battery	2 - 950 CCA
Alternator	150 amps

Capacities

Fuel Tank	379 liters	100 US gallons
Hydraulic Reservoir	114 liters	30 US gallons
Carrying Capacity	2000 kgs	4400 lbs
Deck Size	2800 mm X 1830 mm	110" X 72"

Standard Equipment

- Standard Rear Carrying Deck
- Ergonomic Operator Cab
- 2 Front Suspension Seats
- Cab Heater / Defrost System
- Engine Air Intake Heater
- 2 Heated Rear View Mirrors
- Easy Access Fuse Panel
- Hydraulic Fill Pump with filtration
- 4 Front and 2 Rear Lights (Halogen)
- Electric Cab Tilt with Quick Lock Mechanism
- Roof Exit
- Digital Dash Display
- Audio Visual Alarms
- Rear Window Wiper
- Engine Block Heater
- Strobe Light
- Satellite Stereo System

Optional Equipment

- 8' 6" Wide Front Blade (8 functions)
- Xenon Lighting
- Hydraulic Tank Heater
- Bush Guards
- Off Set Pintle Hook

250 Exportation Street
Tracadie-Sheila, NB
Canada
E1X 1A2

tel.1.888.LAMTRAC
fax.506393.8501
WWW.LAMTRAC.COM