



LAMTRAC



LTR 8400 TWIN

Note: The specifications for a basic vehicle are given on the basis of adequate skills, ability of the operator and under ideal conditions.

Dimensions

Track Width	762 mm	30"
Overall Length	5588 mm	18'4"
Overall Width	2540 mm	8'4"
Overall Height	3149 mm	10'4"
Ground Clearance	508 mm	20"
Weight	12,927 kg	28,500 lbs
Ground Pressure	22.13 KPA	3,21 PSI

Dimensions (with Mulcher)

Track Width	762 mm	30"
Overall Length	6883 mm	22'7"
Overall Width	2743 mm	9'
Overall Height	3149 mm	10'4"
Ground Clearance	508 mm	20"
Weight	15,592 kg	34,374 lbs
Ground Pressure	26.68 KPA	3,87 PSI

Performance

Speed	0-8.5 km/h	0-5.3 mph
Climbing/side Hill	45 °/30°	

Engine

Make	Cummins
Model	QSM 11 Tier III
Horsepower	900hp@2100rpm
Torque	1400 ft/lb@1400rpm

Tracks

Steel, Double Grouser	762 mm	30"
Undercarriage		D4 Equivalent Sealed and Lubricated

Capacities

Fuel Tank	567 liters	150 gallons
Hydraulic Tank	284 liters	75 gallons

Standard Equipment

Front Equipment Mounting Arms
Electronic Joystic Control
Easy Access Fuse Panel and A/C System
Rear Window Wiper
Dome Light
Full Instrumentation
Electronic Engine Control, Fast Idle Control
Audio-Visual Alarm on Major Components
Suspension Seat with Seat Belt
Electric Cab Tilt with Quick Dock Mechanism
ROPS / FOPS/OPS Certified
4 Front and Rear Lights (halogen)
Cab Heater, A/C and Defrost System
Back up Alarm
Engine Block Heater
Roof Exit
Side Exit
Horn
Extinguisher
Centri Engine Air Intake Pre-Filter
Part Book/Operator/Maintenance Manuals
Tool Box
Hydraulic Oil Fill Pump with Transfer Pump

Optional Equipment

Hydraulic Winch
Fire Suspension
Rear View Camera



250 Exportation Street
Tracadie-Sheila, NB
Canada
E1X 1A2

Tel. 1.888.LAMTRAC
Fax. 506.393.8501
www.lamtrac.com